

3½"Coin Acceptor



By combining the best technology and innovation from NRI and Money Controls branded validators outstanding performance and security is guaranteed.





CPI Headquarters
3222 Phoenixville Pike, Suite 200
Malvern, PA 19355 USA
Office: +1 610 430 2700 E-mail: sales@CranePl.com
For additional office locations or product information
please visit www.CranePl.com



3½" Coin Acceptor

Key Features

- Unique MFT coin validation technology for highest coin security
- Simultaneous evaluation of 24 measurement parameters for 32 coin channels
- Protection against string manipulation
- Optical monitoring of coin path for higher security
- Inhibit of single groups or coin groups via DIL switch
- Remote download capabilities
- Multiple interfaces available
- HENRI+ service tool
- Optional hardness detector





Optional Coin Sorter

- · High Sorting Reliability
- 3-way sorter Standard
- 3-way High Speed Sorter s2 HSD 3000

High Security

The Crane Payment Solutions v2 colibri uses the unique MFT Multi-Frequency-Technology to provide the highest coin validation security. The high security provides protection against string manipulation, simultaneous evaluation of 24 measurement parameters for 32 coin channels and optical monitoring of the coin path for higher security.

Flexibility

The v2 colibri is a highly flexible product. The colibri has one step download capabilities and is available with the HENRI+ on site service tool and powerful WinEMP software allowing easy update of coin and configuration data sets. The v2 colibri also features a teach function for up to 8 coins / tokens as standard. Hardware includes both 16 pin and 10 pin connectors for easy machine integration.

Versatility

The v2 colibri is available with multiple machine interfaces including serial S1, serial MDB, ccTalk, parallel and SGI (Simple Gaming Interface) with fast coin acceptance for casino applications. Accessories for the v2 colibri include front plates, sorters and a wake-up sensor for low power applications. There is also an option for coin changer compatible housing (long channel).

• Industry Standard Mount

Optional Front-Plates

- Front-Plate & Mini-Front-Plate
- Choice of Colours

Technical Data: GENERAL

Currencies	All world currencies
Dimensions HxWxD mm (in)	102 (4) x 89 (3.5) x 52 (2)
Coin Dimensions mm	
Diameter	15 to 31.5 (option up to 32.5)
Thickness	1.5 to 2.5 (option up to 3.3)
Power Supply	
Voltage DC	12 to 24 +/-10% (option10 to 48)
Temperature	
Operating	0°C to 55°C
Storage	-25°C to 70°C



Henri+

- On site service tool
- Easy update of coin and configuration data sets



E&OE